

UTF MAX SERIES

UTF MAX SERIES es un aceite lubricante multiusos de alto rendimiento diseñado para cumplir o exceder los requisitos de transmisión y fluido hidráulico. UTF MAX está diseñado para optimizar el rendimiento de los tractores agrícolas y comerciales que operan en una amplia gama de entornos y condiciones.

UTF MAX SERIES combines top quality base oils and advanced technology additives to deliver the versatile lubricant performance properties required in severe duty applications of agricultural and construction equipment.

UTF MAX SERIES is specially recommended for today's power train transmissions, drive axles, clutches, PTOs and hydraulic systems.

Physical Properties

PRODUCTS	10W30
Viscosity @ 40°C, cSt @ 100°C, cSt	55 9.3
Brookfield Viscosity, cP (@ -20°C)	4300
Flash Point, (°C) ASTM D92	198
Drop Point, (°C) ASTM D97	-42
Density @15 °C kg/l ASTM D4052	0.88

Shelf Life: *Product shelf life is 5 years from the date of manufacture, after which the product should be recertified prior to*

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.