

# Product Data Sheet

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

## DELTA MAX SAE 15W-50

*Delta Max SAE 15W-50 la mezcla sintética es un aceite de motor de alto rendimiento para vehículos modernos y motores estacionarios, producido con un paquete aditivo avanzado que garantiza un menor engrosamiento del aceite; mejor oxidación y resistencia a la corrosión, menos desgaste y mejora el rendimiento integral.*

*Delta Max SAE 15W-50 es especialmente eficaz en los motores de vehículos comerciales y el servicio de flota mixta donde se utilizan vehículos de modelo moderno, particularmente cuando trabajan en condiciones extremas. Cumple con las normas ambientales actuales EURO 5/4/3/2 y se puede utilizar en motores con tecnologías de limpieza de gases de escape EGR y/o SCR sin filtro de partículas.*

*Delta Max SAE 15W-50 meets and exceeds with the following manufacturers specifications:*

API CI-4+/SL	ACEA A3/B4, E7
MB 228.3	MB 229.1
Volvo VDS-3	Mack EO-M Plus / EO-N
RENAULT VI, RLD-2	Cummins CES 20071/-72/-75/-76/-77/-78
MAN M 3275	MTU 2
IVECO	Caterpillar ECF-1-a
ALLISON C-4	Voith Retarder Typ A

## Physical Properties

PRODUCT	15W-50
SAE Grade	15W-50
Viscosity:	
@ 40°C, cSt	132.6
@ 100°C, cSt	18.3
Viscosity Index	155
Specific Gravity	0.866
Flash Point, °C	206
Pour Point, °C	-36
Total Base #, mg KOH/g	10.7

**Shelf Life:** Delta Max 15W50 product have a 5 years shelf life. Shelf life is from the date of manufacture, after which the product should be recertified prior to use.

Manufactured by Klüber Lubrication NA LP • P.O. Box 131359 • Tyler, CR 2120, Texas 75713, under license from Brautek LLC

# Product Data Sheet

**NOTE:** The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.



SYNTHETIC BLEND INDUSTRIAL GEAR OIL