

**Product Data Sheet**

Manufactured by Klüber Lubrication NA LP • P.O. Box 131359 • Tyler, CR 2120, Texas 75713, under license from Brautek LLC

**NOTE:** The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

## THERMOMAX SERIES

*Brautek Thermo Max 46 son medios de transferencia de calor de altacalidad hechos de aceites base de mezcla sintética. Son muy resistentes al agrietamiento térmico y a la descomposición y tienen una excelente estabilidad térmica.*

*Brautek Thermo Max 46 se recomiendan para su uso en instalaciones indirectas de calefacción y refrigeración en todo tipo de procesos industriales que operan a temperaturas de aceite a granel. The high thermal stability of*

*Brautek ThermoMax Series will reduce the tendency towards viscosity increase in correctly designed indirect heating systems and prevent formation of deposits which interfere with efficient heat transfer operations.*

### Physical Properties

PRODUCTS	32	46	68
ISO Grade	32	46	68
Viscosity @ 40°C, cSt	31.0	45.5	67.0
Viscosity @ 100°C, cSt	5.36	6.9	8.92
Viscosity Index	106	106	106
Flash Point, °C	225	230	243
Pour Point, °C	-15	-12	-17
Specific Gravity @ 15 °C kg/l, ASTM D 4052	0.878	0.878	0.87

**Shelf Life:** Product shelf life is 5 years from the date of manufacture, after which the product should be recertified prior to use.