

Product Data Sheet

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

DELTA MAX SAE 15W-40

Delta Max SAE 15W-40 synthetic blend is a highly effective engine oil of a new level of modern vehicles and stationary engines, which is a product of the evolution of API CI-4+ oil to higher requirements of ACEA E7.

Delta Max SAE 15W-40 is produced with the use of an advanced and balanced additive package which allows to ensure optimum productivity, thermal, viscosity and antioxidant stability during a long period of exploitation.

Delta Max SAE 15W-40 is especially effective in engines of commercial vehicles, medium-loaded engines of main trucks, agricultural and quarry equipment. Complies with the current environmental standards EURO 5/4/3/2 and can be used in engines with EGR and/or SCR exhaust gas cleaning technologies without a particulate filter.

Delta Max SAE 15W-40 meets and exceeds with the following manufacturers specifications:

API CI-4+/SL	ACEA A3/B4, E7
MB 228.3	MB 229.1
Volvo VDS-3	Mack EO-M Plus / EO-N
RENAULT VI, RLD-2	Cummins CES 20071/-72/-75/-76/-77/-78
MAN M 3275	MTU 2
IVECO	Caterpillar ECF-1-a
ALLISON C-4	Voith Retarder Typ A

Physical Properties

PRODUCT	15W-40
SAE Grade	15W-40
Viscosity:	
@ -20°C, mPa.s	6100
@ 100°C, cSt	15.6
Viscosity Index	143
Specific Gravity	0.874
Flash Point, °C	220
Pour Point, °C	-32
Total Base #, mg KOH/g	10.7

Shelf Life: Delta Max 15W40 product have a 5 years shelf life. Shelf life is from the date of manufacture, after which the product should be recertified prior to use.