

GUIDEMAX SERIES

Brautek Guide Max 32 son lubricantes deslizantes de primera calidad específicamente de diseño para satisfacer los recuestramentos para la precisión, la separabilidad acuosa del refrigerante y la protección del equipo de las máquinas herramienta de precisión. Están formulados a partir de bases de mezcla sintéticas y el rendimiento equilibrado con un avanzado sistema de aditivos que proporcionan propiedades de fricción controladas, compatibilidad con fluidos metalúreos acuosos y protección contra la corrosión de piezas y equipos.

Guide Max Series provides the following benefits:

- Helps eliminate stick slip; allows consistently accurate machining.
- Suitable for a wide range of way material combinations allowing for product consolidation.
- Prevents removal of lubricants from critical surfaces.
- Help to reduce the deterioration of sliding surface.

Physical Properties

PRODUCTS	GUIDE-32	GUIDE-68	GUIDE-220
ISO Grade	32	68	220
Viscosity			
@ 40°C, cSt	32.68	68	220
@ 100°C, cSt	5.38	8.57	18.82
Viscosity Index	97	96	96
Specific Gravity	0.8767	0.8863	0.8848
Flash Point, °F	428	428	464
(°C)	(220)	(220)	(240)
Apparence	Yellow	Yellow	Yellow

Shelf Life: Product shelf life is 5 years from the date of manufacture, after which the product should be recertified prior to use.

Manufactured by Klüber Lubrication NA LP • P.O. Box 131359 • Tyler, CR 2120, Texas 75713, under license from Brautek LLC

Product Data Sheet

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.