

Product Data Sheet

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

HYMAX HD 10W

HyMax HD 10W es un aceite de mezcla sintético utilizado para la racionalización necesaria de lubricantes, sobre todo para flotas de vehículos y equipos. El aceite del motor adecuado está disponible con HyMaxHD 10W. Ya sea continuamente a toda velocidad o en STOP y GO operation, HyMaxHD 10W proteja contra el desgaste, depósitos y corrosión todo el tiempo con el menor consumo de aceite. Otro punto importante para su uso en la práctica: motores lubricados con Nocirificios De 10W have en rendimiento debido a depósitos no permitidos en las combustion chambers. HyMaxHD 10W provuros para la función adecuada de los cargadores de válvulas hidráulicas (compensación de válvula hidráulica) incluso durante los intervalos de cambio de aceite extendidos.

HyMax HD 10W is miscible and compatible with conventional branded engine oils. However, mixing with other engine oils should be avoided in order to fully utilize the product's benefits. HyMax HD 10W meets and exceeds with the following manufacturers specifications:

ACEA E2 MIL-L-2104 D	API CF/CF-2
CAT TO-2ZF TE-ML	ALLISON C-4MB
02CZF TE-ML 03B	228.0 MAN 270
(ZF002013)	

Physical Properties

PRODUCTS	HD-10W
SAE Grade	10W
Viscosity	
@ 40°C, cSt	37.7
@ 100°C, cSt	6.1
Viscosity Index	107
Specific Gravity	0.873
Flash Point, °C	232
Pour Point, °C	-30
Total Base #, mg KOH/	4.0
Sulfated Ash, wt%	0.5

Shelf Life: HyMax AW Series products have a 5 years shelf life. Shelf life is from the date of manufacture, after which the product should be recertified prior to use.